NON-CAP-SENSITIVE · PACKAGED EMULSION

Neo Base

TECHNICAL DATASHEET

Neo Base is a high-strength, non-cap-sensitive packaged emulsion explosive with a firm, putty-like consistency. It is sensitized using chemical gassing, microspheres, or a combination of both, producing a stable emulsion matrix with excellent water resistance for reliable use in wet or flooded boreholes.



1.2 ± 0.05 g/cc	80 %	115 %	4000 ± 300 m/s
DENSITY	RELATIVE WEIGHT STRENGTH	RELATIVE BULK STRENGTH	VELOCITY OF DETONATION

RWS and RBS are calculated relative to ANFO at a density of 0.8 g/cc.

PRODUCT OVERVIEW

Being non-cap-sensitive, it requires initiation through a suitable primer or booster and is primarily intended for use as a column explosive in surface mining, underground operations, quarrying, tunnelling, and civil construction blasting. It is particularly suited for medium to large diameter boreholes where high-energy column charges are required.

The cartridges are packed in durable, tear-resistant film that maintains their shape during handling and loading, ensuring ease of charging and reliable performance under field conditions.

KEY BENEFITS

- High energy output with strong pre-compression resistance, ensuring consistent blasting performance in hard and confined ground conditions.
- Excellent water resistance, allowing reliable use in wet and water-logged boreholes without loss of energy.
- High velocity of detonation and strong weight strength for superior fragmentation and overall blast efficiency.
- Suitable as a column explosive for medium to large diameter boreholes in mining, quarrying, tunnelling and civil construction.
- High viscosity and rigidity help maintain cartridge shape and ensure smooth loading.
- Minimizes leaching, reducing environmental impact in sensitive areas.

OFFICE
A-608, WALLFORT ENCLAVE-2, PACHPEDI NAKA
RAIPUR CHHATTISGARH 492001

PHONE
+91 9993555756

EMAIL
sivatradeandpack1@gmail.com

RECOMMENDATIONS FOR USE

- Suitable for blasting in dry, wet, and water-filled boreholes.
- Must be initiated using a suitable primer or booster with an approved electric or non-electric initiation system.
- Recommended for use as a column explosive in medium to large diameter boreholes.
- Ensure the primer is positioned in accordance with the blast design to achieve reliable initiation of the explosive column.
- Use wooden or non-metallic loading/tamping tools where required.
- Ensure adequate ventilation before re-entry following underground blasting operations.
- Avoid excessive heat, impact, friction, or contamination during handling and charging.
- Suitable for ground temperatures ranging from –5°C to 50°C. For applications outside this range, consult the manufacturer or technical representative.

CARTRIDGE SPECIFICATIONS

Diameter (mm)	Mass (g)	Units / Box
83	2780	9
125	6250	4
200	12500	2

SAFETY & STORAGE

- Store in a cool, dry, well-ventilated, licensed magazine approved for Class-2 explosives.
- Avoid exposure to high temperatures, direct sunlight, or freezing conditions, as extreme temperatures may reduce shelf life or alter performance.
- Maintain proper inventory rotation: always use the oldest stock first.
- Shelf life is generally 12 months under recommended storage conditions; deterioration may occur sooner if exposed to heat, moisture, or rough handling.
- Protect cartridges from shock, friction, or mechanical impact to prevent accidental initiation.
- Dispose of deteriorated or damaged explosives as per local regulations and under supervision of authorized personnel.

TRANSPORT

Transport Classification	Class	UN Number
Standard Packaging	1.1D	UN 0241

PRODUCT DISCLAIMER

© 2026 Siva Trade and Pack. All rights reserved. The details presented in this document (“Information”) are intended to provide general technical guidance regarding the referenced products (“Products”). While reasonable care has been taken in compiling this Information, Siva Trade and Pack does not guarantee its accuracy, consistency, or applicability to every operational environment, and the Information may be updated or amended without prior notice.

Explosive Products must only be handled, transported, and used by personnel who are properly trained, certified, and authorized to work with such materials. Users are responsible for assessing site-specific conditions, verifying regulatory requirements, and ensuring that all procedures align with applicable safety standards and legal obligations.

To the extent permitted by law, Siva Trade and Pack rejects any form of warranty — statutory, express, or implied — relating to the Information or the Products, including but not limited to performance guarantees or suitability for a particular use. The company shall not be held liable for any loss, damage, injury, or operational consequence arising from reliance on this Information or from misuse or improper handling of the Products. This document is provided solely for reference and shall not be interpreted as a contractual commitment, product guarantee, or legally binding representation by Siva Trade and Pack.

OFFICE
A-608, WALLFORT ENCLAVE-2, PACHPEDI NAKA
RAIPUR CHHATTISGARH 492001

PHONE
+91 9993555756

EMAIL
sivatradeandpack1@gmail.com