CAP-SENSITIVE · PACKAGED EMULSION

Neo Prime

TECHNICAL DATASHEET

Neo Prime is a high-strength, cap-sensitive packaged emulsion explosive with a firm, putty-like consistency. It is sensitized using chemical gassing, microspheres, or a combination of both, providing a stable and reliable energy output. The emulsion matrix offers excellent water resistance, allowing dependable performance in wet or partially flooded boreholes.



1.15 ± 0.05 g/cc	118 %	166 %	4400 ± 300 m/s
DENSITY	RELATIVE WEIGHT STRENGTH	RELATIVE BULK STRENGTH	VELOCITY OF DETONATION

RWS and RBS are calculated relative to ANFO at a density of 0.8 g/cc.

PRODUCT OVERVIEW

Neo Prime is designed for priming duties as well as use as a column explosive in surface mining, underground operations, quarrying, tunnelling, and general construction blasting. Its high detonation velocity and robust formulation make it highly effective for initiating ANFO columns and other non-cap-sensitive bulk or packaged explosives.

The cartridges are packed in durable, tear-resistant film that maintains shape during handling and ensures stability during water rise. This makes it suitable for demanding blasting conditions where consistent initiation and strong explosive energy are required.

KEY BENEFITS

- High energy output with strong pre-compression resistance, ensuring consistent blasting performance in hard and confined ground conditions.
- Excellent water resistance, allowing reliable use in wet and water-logged boreholes without loss of energy.
- High velocity of detonation and strong weight strength for superior fragmentation and overall blast efficiency.
- Safe to manufacture, transport, store, and handle — classified as an oxidizer, reducing risk during non-blasting stages.
- Suitable for use as a primer, offering a cost-effective and safer alternative to cast/emulsion boosters.
- High viscosity and rigidity help maintain cartridge shape and ensure smooth loading even in varied hole conditions.
- Minimizes leaching, reducing environmental impact in sensitive areas.

OFFICE
A-608, WALLFORT ENCLAVE-2, PACHPEDI NAKA
RAIPUR CHHATTISGARH 492001

PHONE
+91 9993555756

EMAIL
sivatradeandpack1@gmail.com

RECOMMENDATIONS FOR USE

- Suitable for blasting in dry, wet, and watery holes.
- Can be initiated using electric or non-electric detonators (minimum No. 8 strength) or detonating cord of 5 g/m PETN or higher, as per product specification.
- Achieve maximum energy output by proper tamping using a wooden or non-metallic tamping rod.
- Do NOT tamp a primer cartridge containing a detonator.
- Post-blast fumes are generally suitable for surface and underground applications, but ensure adequate ventilation before re-entry.
- Avoid excessive shock, heat, friction, or mechanical impact to prevent premature initiation.
- Suitable for ground temperatures in the range -5°C to 50°C. For operations outside this range, seek guidance from the manufacturer or technical representative.

CARTRIDGE SPECIFICATIONS

Diameter (mm)	Length (mm)	Mass (g)	Units / Box
60	320 ± 5	1000	25
65	340 ± 5	1250	20
70	410 ± 5	2080	12
90	450 ± 5	2780	09

SAFETY & STORAGE

- Store in a cool, dry, well-ventilated, licensed magazine approved for Class-2 explosives.
- Avoid exposure to high temperatures, direct sunlight, or freezing conditions, as extreme temperatures may reduce shelf life or alter performance.
- Maintain proper inventory rotation: always use the oldest stock first.
- Shelf life is generally 12 months under recommended storage conditions; deterioration may occur sooner if exposed to heat, moisture, or rough handling.
- Protect cartridges from shock, friction, or mechanical impact to prevent accidental initiation.
- Dispose of deteriorated or damaged explosives as per local regulations and under supervision of authorized personnel.

TRANSPORT

Transport Classification	Class	UN Number
Standard Packaging	1.1D	UN 0241

PRODUCT DISCLAIMER

© 2026 Siva Trade and Pack. All rights reserved. The details presented in this document ("Information") are intended to provide general technical guidance regarding the referenced products ("Products"). While reasonable care has been taken in compiling this Information, Siva Trade and Pack does not guarantee its accuracy, consistency, or applicability to every operational environment, and the Information may be updated or amended without prior notice.

Explosive Products must only be handled, transported, and used by personnel who are properly trained, certified, and authorized to work with such materials. Users are responsible for assessing site-specific conditions, verifying regulatory requirements, and ensuring that all procedures align with applicable safety standards and legal obligations.

To the extent permitted by law, Siva Trade and Pack rejects any form of warranty — statutory, express, or implied — relating to the Information or the Products, including but not limited to performance guarantees or suitability for a particular use. The company shall not be held liable for any loss, damage, injury, or operational consequence arising from reliance on this Information or from misuse or improper handling of the Products. This document is provided solely for reference and shall not be interpreted as a contractual commitment, product guarantee, or legally binding representation by Siva Trade and Pack.

OFFICE
A-608, WALLFORT ENCLAVE-2, PACHPEDI NAKA
RAIPUR CHHATTISGARH 492001

PHONE
+91 9993555756

EMAIL
sivatradeandpack1@gmail.com